

Whether you're in a climate that's hot year-round or just in the sticky summer months, Air Con service represents huge potential. With solutions for everything from standard to YF and hybrid applications, we help you capitalize on the opportunity. Our Air Con units provide advanced features, unmatched accuracy & simple operation. **Talk to your Snap-on Dealer about a Sun AIR CON unit that suits your needs.**

Limited Offer

Includes
26 Can Cooler Box

With Each AIR CON unit purchased. Offer Effective September - December 2019



Blizzard (Automatic)
EEACEU126A (R134A)
Blizzard with Leak Check
*EEACEU127AS (R134A)
*EEACEU128AS (HFO)

Blizzard Pro (Automatic) with Leak Check & KoolKlean
*EEACEU127A (R134A)
*EEACEU128A (HFO)

Dual (Automatic) with Leak Check
*EEACEU124C (R134A & HFO)

Breeze (Semi-Auto)
EEACEU129A
*EEACEU130A

Truck (Automatic) with Leak Check
EEACEU118C (R134A)

SOFTWARE: EESP-DBAUTO2



Accessories



| Technical data | Blizzard | Blizzard Pro | Blizzard HFO | Dual Gas | Breeze III | Breeze III-HFO | HD-Truck |
|--|------------------------|------------------------|------------------------|------------------------|-----------------------|-----------------------|------------------------|
| Model # | EEACEU126A | *EEACEU127A (S) | *EEACEU128A (S) | *EEACEU124C | EEACEU129A | *EEACEU130A | EEACEU118C |
| Type of refrigerant | R134a | R134a | HFO1234yf | R134-HFO1234yf | R134a | HFO1234yf | R134a |
| Service Procedure | Fully Automatic/manual | Fully Automatic/manual | Fully Automatic/manual | Fully Automatic/manual | Semi Automatic/manual | Semi Automatic/manual | Fully Automatic/manual |
| Air Purge | Automatic | Automatic | Automatic | Automatic | Manual | Manual | Automatic |
| Heated Cylinder | Yes | Yes | Yes | Yes | Yes | Yes | No |
| Filters | 1 | 1 | 1 | 2 | 1 | 1 | 2 |
| Vacuum Pump Capacity | 100 l/min/0.1 mbar | 100 l/min/0.1 mbar | 100 l/min/0.1 mb | 100 l/min/0.1 mb | 100 l/min/0.1 mbar | 100 l/min/0.1 mb | 170 l/min/0.1 mbar |
| Recovery Speed liquid phase | 300g/min | 300g/min | 300g/min | 300g/min | 300g/min | 300g/min | 300g/min |
| Recovery/refrigerant cylinder capacity | 22L refillable | 22L refillable | 12L refillable | 2x12L refillable | 12L refillable | 12L refillable | 40L refillable |
| Display Screen | 5" colour | 5" colour | 5" colour | 7" colour (touch) | LCD (98X39mm) | LCD (98X39mm) | LCD (123x40mm) |
| Weight (kg) | 90 | 90 | 90 | 110 | 90 | 90 | 140 |
| Refillable Hermetic Pag oil & dye containers | 1 oil + 1 dye | 1 oil + 1 dye | 1 oil + 1 dye | 2 oil + 2 dye | 1 oil + 1 dye | 1 oil + 1 dye | 1 oil + 1 dye |
| Oil change procedure | Yes | Yes | Yes | Yes | No | No | No |
| Hybrid function | No | Yes | Yes | Yes | No | No | No |
| Automatic dye injection | Yes | Yes | Yes | Yes | Yes | Yes | Yes |
| Vehicle database | Yes | Yes | Yes | Yes | Yes | Yes | Yes |
| Automatic Vacuum Leak Check | Yes | Yes | Yes | Yes | Yes | Yes | Yes |
| Service Hose length | 3m | 3m | 3m | 2 pairs, 3m each | 3m | 3m | 6m |
| On-board printer | Yes | Yes | Yes | Yes | Yes | Yes | Yes |
| Refrigerant management | Yes | Yes | Yes | Yes | Yes | Yes | Yes |
| Static diagnosis | Yes | Yes | No | No | yes | No | No |
| Refrigerant Pump 1kg/min | No | No | No | No | No | No | Yes |
| Nitrogen Leak Check | No | Yes | Yes | Yes | No | No | Yes |
| *KoolKlean External Unit package | No | Yes (S - No) | Yes (S - No) | No | No | No | No |
| Status light | No | Yes | Yes | No | No | No | No |
| Flushing operation (SW) | Yes | Yes | Yes | Yes | Yes | Yes | No |
| Automatic Taps | Yes | Yes | Yes | Yes | No | No | No |